



**Performance Level: BEST**  
**Warranty: 10 Year**

Refer to Data Sheet 663.0  
 Antimicrobial Product Protection



## LATICRETE® Hydro Ban™

LATICRETE invented and set the standard for thin load-bearing waterproofing membranes over 40 years ago. We have now re-invented the category again! LATICRETE® Hydro Ban™ is a revolutionary new waterproofing/anti-fracture membrane for commercial or residential applications. No other waterproofing membrane offers such incredible features as:

- No fabric required in the field, coves or corners
- Allows for flood testing in only 24 hours at 21°C (70°F)
- Bonds directly to metal and PVC drain pipes and penetrations
- Paint brush, roll, trowel or airless spray applied
- One component, very low odor, water cleanable
- Exceeds ANSI A118.10 and ANSI A118.12 requirements

### PACKAGING

#### Commercial Unit

18.9 ℓ (5 gallon) pail liquid; 36 units per pallet.

#### Full Unit

7.6 ℓ (2 gallon) pail liquid; 80 units per pallet.

#### Mini Unit

3.8 ℓ (4 x 1 gallon) pails of liquid packed in a carton; 30 cartons per pallet.

APPROXIMATE COVERAGE	
Per Commercial Unit	23.2 m <sup>2</sup> (250 ft <sup>2</sup> )
Per Full Unit	9.3 m <sup>2</sup> (100 ft <sup>2</sup> )
Per Mini Unit	4.7 m <sup>2</sup> (50 ft <sup>2</sup> )



## LATICRETE 9235 Waterproofing Membrane

LATICRETE 9235 Waterproofing Membrane is “The Industry Standard” for wet areas and continuous water submersion applications. Applies with a paint roller or brush, cures in just hours and provides a permanent waterproofing base for tile, glass mosaic and stone in pools, showers and spas. LATICRETE 9235 Waterproofing Membrane is accepted by IAPMO and ICC for shower pans, meets ANSI A118.10 and ANSI A118.12, is non-hazardous and meets all VOC requirements. When anti-fracture treatment is required in wet areas, LATICRETE 9235 Waterproofing Membrane provides the complete package. You only need one product to protect your floor from water damage and substrate cracks. Inhibits the growth of stain-causing mold and mildew in membranes with antimicrobial product protection. “Extra Heavy” service rating per ASTM C627 (TCNA).

### PACKAGING

#### Full Unit

23 ℓ (6 gallon) pail of liquid, 1 carton LATICRETE Waterproofing/Anti-Fracture Fabric, packed separately; 36 units per pallet.

#### Mini Unit

7.6 ℓ (2 gallon) jug of liquid, and LATICRETE Waterproofing/Anti-Fracture Fabric packed together in one pail; 48 pails per pallet.

APPROXIMATE COVERAGE	
Per Full Unit	28 m <sup>2</sup> (300 ft <sup>2</sup> )
Per Mini Unit	7 m <sup>2</sup> (75 ft <sup>2</sup> )



**Performance Level: BEST**

**Warranty: 10 Year**

Refer to Data Sheet 236.0  
Antimicrobial Product Protection



## LATICRETE 9237 Waterproofing Membrane

A light duty, single component, roller-applied waterproof membrane for use under thin and thick bed installations of ceramic tile and stone, and other finishes. Economical, thin, safe, solvent-free; and cleans up with water while fresh. Does not require fabric reinforcing except for corners, coves, and certain other applications.

### PACKAGING

20 ℓ pail (5 gal); 36 pails per pallet.

### COVERAGE

Approximately 13 – 20 m<sup>2</sup> per 20 ℓ pail (150–225 ft<sup>2</sup>).

**NOTE: LATICRETE® 9237 Waterproofing Membrane liquid is applied in 2 coats. Coverage varies based on substrate texture, porosity, and application technique.**



**Performance Level: GOOD**

Refer to Data Sheet 641.0